

Index

A

- acbuf, 15-31
- accumulation buffer, 15-30 through 15-36
- acsize, 15-30
- addressing
 - frame buffer memory, 6-1
 - frame buffers, 10-1
 - pixels, 11-4
- afunction, 8-22, 18-45
- algebraic representations, 14-2
- aliasing, definition of, 15-1
- ALPHA, 9-21
- alpha
 - bitplanes, 15-7
 - blending, 8-22 through 8-26
 - hints for texture, 18-45
 - of material, 9-21
- AMBIENT, 9-8, 9-9
- ambient light, 9-4, 9-9
- ambient property, fast update of, 9-20
- animation, 6-1 through 6-8
 - flicker, 6-2
 - frame rate, 6-3
 - gsync not recommended, 6-8
 - maximizing performance, 6-6
 - setting swap interval for, 6-7
 - setting up, 6-3
- anomalies, display, 2-20
- ANSI C, 1-1, 1-4
 - cckr non-ANSI compatibility flag, 1-4
- antialiasing, 15-1 through 15-36
 - box filter, 15-35
 - definition, 15-1
 - Gaussian filter, 15-35
 - lines, 15-15
 - multipass, 15-30 through 15-36
 - onepass, 15-10 through 15-30
 - on RealityEngine, 15-36 through 15-47
 - polygons, 15-22
 - RGB lines caution, 15-22
 - RGB mode, 15-13
 - subpixel, 15-4 through 15-5
- approximating surfaces
 - non-planar polygons, 2-16
- apropos*, xxv
- arc/arcf, 2-36
- arcs, 2-35
- aspect ratio, 7-5
 - maintaining, 7-6
- asymmetric viewing volume, 7-9, 7-11
- Athena widgets, 5-2
- atmospheric effects, 13-10 through 13-14
- attachcursor, 5-6
- ATTENUATION, 9-15
- ATTENUATION2, 9-15

C

- `cc`, 1-4
- `-cckr`, 1-4
- `c3s`, 4-7
- caching of texture memory, 18-45
- calculations, precision of, 2-16
- callbacks limited for remote operation, 19-5
- `callfunc`, 19-5
- `callobj`, 16-4
- Cardinal spline curve, 14-29
- cartesian floating point coordinates, 7-2
- C compiler, 1-4
- changing currently bound definitions, 9-13
- changing defined objects, 16-8
- changing lighting settings, 9-12 through 9-13
- changing pixel fill directions, 11-12
- changing the color map, 4-16
- character, 3-2
 - bitmasks, 3-8
 - clipping, 3-4
 - transformations, 3-6
- `charstr`, 3-2
- choosing items on the screen, 12-1
- choosing parameters for `ortho`, 7-11
- chunk, 16-13
- `chunksize`, 16-12
- `circ/circonf`, 2-34
- circle, representing with NURBS, 14-12
- circles, 2-34
- clearing stencil planes, 8-19
- client/server model, 19-1
- clip coordinates, 7-3
- clipping
 - characters, 3-4
 - effect on feedback, 17-3
 - gross, 3-4
 - clipping planes, 7-5, 7-8, 7-9, 8-7
 - user-defined, 7-30
- `clipplane`, 7-30
- `clkoff`, 5-16
- `clkon`, 5-16
- closed line, definition, 2-8
- `closeobj`, 16-2, 16-8
- closing an object definition, 16-2
- closing a window, 5-14
- `cmov`, 3-2
- coefficients, 14-5
- color, 4-1 through 4-25
 - blending, 15-5 through 15-9
 - how monitors display, 4-2
 - how the GL calculates for lighting, 9-6
 - in lighted scenes, 9-2
 - mode, 4-3
 - NURBS surface, 14-13, 14-17
 - smooth variation, 4-9
- `color`, 4-17, 10-5
- color data, 8-bit, 4-5
- color display correction, 4-23
- `colorf`, 4-17
- color guns, 4-2
- color index, 4-17
- color index mode, see color map mode
- color map
 - assigning in multimap mode, 4-22
 - changing, 4-16
 - default, 4-16
 - getting index of in multimap mode, 4-22
 - getting values of, 4-18
- color map mode, 4-15 through 4-20
 - antialiased points, 15-11
 - depth-cueing, 13-4
 - lighting, 9-24
 - querying, 4-22
- color mode
 - querying, 4-8

- color ramp, 13-5
- compactify, 16-12
- compatibility, 1-9
 - GLC_OLDPOLYGON, 2-31
- compiling C programs, 1-4
- concave, 2-13
- concave polygon, 2-13
- configuration, remote, 19-12
- configuring overlay/underlay
 - bitplanes, 10-15 through 10-17
- conic sections, representing
 - with NURBS, 14-12
- connection, 19-4
 - default, 19-4
 - permission, 19-4
 - TCP, 19-12
- contour texture, 18-35
- control net, 14-13
- control points, 14-5, 14-6
 - agree with data type, 14-15
 - size of array, 14-14
- control polygon, 14-6
- convex polygon, 2-12
- coordinates
 - cartesian, 7-2
 - clip, 7-3
 - eye, 7-3
 - normalized, 7-3
 - object, 7-2
 - window, 7-3
 - world, 7-3
- coordinate systems, 7-2 through 7-3
- copying pixels, 11-7
- correlated blending function, 15-26
- cpack, 4-7
- C programming language, xxi, 1-4
- creating a cursor, 10-19
- creating a font, 3-7 through 3-10
- creating a glowing surface, 9-4

- creating an object, 16-2
- creating highlights with lighting, 9-3
- creating queue entries, 5-4
- cross-hair cursor, 10-17
- cross-plot, 14-4
- cubic polynomials, 14-5
- culling
 - definition, 16-5
 - NURBS, 14-21
- curorigin, 10-20
- current character position, 3-2
 - finding, 3-4
- current graphics position, 2-37
- current matrix, 7-16
- current normal, 9-5
- current texture matrix, 18-33
- cursoff, 5-6
- curson, 5-6
- cursor, 5-6
 - creating, 10-19
 - cross-hair, 10-17
 - default, 10-17
 - defining a glyph, 10-20
 - defining the type, 10-20
 - finding, 5-7
 - hardware, 10-17
 - mask, 10-17
 - mode, 10-6
 - origin, 10-20
 - turning on/off, 5-6
 - types, 10-17
- cursor devices, 5-13
- CURSORDRAW, 10-6
- cursors, 10-17 through 10-23
- curstype, 10-20
- curves
 - old-style, 14-28, 14-28 through 14-33
- cyclemap, 4-22
- czclear, 8-8, 8-9

D

- daemon, 19-12
 - dgl*, 19-13
 - inetd*, 19-13
- dbtext, 5-17
- decals, 18-42
- default connection for remote operation, 19-4
- default cursor, 10-17
- default settings for lighting, 9-13
- defcursor, 10-20
- defining a screen region for selecting, 12-8
- defining a cursor glyph, 10-20
- defining a material, 9-8
- defining a viewing point, 7-13
- deflinestyle, 2-10
- defpattern, 2-16
- defrasterfont, 3-8
- degree elevation of polynomials, 14-5
- deleting an object, 16-4
- delobj, 16-4
- deltag, 16-10
- demos
 - NURBS Curve*, 14-1
 - Trimmed NURBS*, 14-1
- density of fog, 13-12
- dependent variable, 14-2
- depth-cueing, 13-1 through 13-10
 - in color map mode, 13-4
 - optimizing resolution for, 7-5
- depth-cueing in RGB mode, 13-6
- DEPTHCHANGE, 5-14
- depthcue, 13-4
- depth perception, 13-1
- DetailTexture, 18-27 through 18-32
- determining the maximum z value, 8-7
- determining the minimum z value, 8-7

- device
 - disabling queuing, 5-4
 - finding out if queued, 5-4
 - initialization, 5-16
 - queueing, 5-4
 - Spaceball, 5-15
- device domain, 5-10
- devices, 5-10 through 5-17
 - ghost, 5-13
 - labeling dial and button box, 5-17
- DGL client, 19-2
- dgl* daemon, 19-13
- DGL protocol, 19-2, 19-12
- DGLSERVER, 19-4
- DGL server, 19-2
- DGLTsocket, 19-4
- DGLTYPE, 19-4
- dial and button box, 5-17
- difference image, 18-28
- DIFFUSE, 9-8
- diffuse reflectance, 9-3
- diffuse reflection, fast update, 9-20
- disabling queueing for a device, 5-4
- discontinuity, 14-8
- DISPLAY, 1-2, 1-3, 19-4
- display
 - getting mode, 6-7
 - hostname, 1-3
- display anomalies, 2-20
- displaying graphics over the network, 19-1 through 19-16
- display lists, 16-1
- distance-squared attenuation, 9-15
- distortion
 - from non-planar polygons, 2-16
 - in color displays, 4-23
- dither, 4-4
- dithering, 4-4

- doublebuffer, 6-2
- double buffering, 6-1
- double buffer mode, 6-1, 6-2
- draw, 2-39
- drawing, 2-1 through 2-37, 3-2
 - arcs, 2-35
 - characters, 3-2
 - circles, 2-34
 - cursors, 10-17 through 10-23
 - meshes, 2-21 through 2-28
 - mode, 10-5 through 10-7
 - object in display list, 16-4
 - old-style, 2-30 through 2-42
 - on top of pixels, 10-1
 - points, 2-7
 - polygons, 2-15
 - polylines, 2-8
 - rectangles, 2-32
 - setting bitplane destination, 10-5
 - underneath pixels, 10-1
- drawing mode, 10-1
- drawmode, 10-6
 - pixel access, 11-4
- driving a plotter with feedback, 17-2

E

- 8-bit color data, 4-5
- editobj, 16-8
- effect of clipping on feedback, 17-3
- electrons, 4-2
- emission, 9-4
- EMMISSION, 9-9
- emptying the event queue, 5-3
- enabling queueing for a device, 5-4
- enclosedline, 2-9
- endline, 2-8
- endpick, 12-2

- endpoint, 2-7
- endpolygon, 2-15
- endqstrip, 2-27
- endselect, 12-8
- ENDTAG, 16-9
- endtmesh, 2-21
- environment variable
 - DISPLAY, 1-2
- environment variables
 - for remote operation, 19-4
- equation
 - depth-cued color, 13-6
 - fog, 13-12
 - size of control point array for NURBS, 14-14
- error
 - floating point, 2-16
 - roundoff, 2-4
- error messages
 - remote, 19-13
- establishing a remote connection, 19-4
- Ethernet, 19-2
- eye coordinate system, 7-3

F

- 4Dwm, 1-2, 1-3
- fast updates to material, 9-18
- fat polygons, 2-19
- feedback, 17-1 through 17-10
 - data types, 17-2
 - effect of clipping, 17-3
 - IRIS-4D/GT/GTX, 17-4
 - IRIS-4D/VGX, 17-7
 - IRIS Indigo, 17-6
 - Personal IRIS, 17-6
 - sample program, 17-8
- feedback, 17-2
- field of view, 7-5

- finding out if a device is queued, 5-4
- finding the cursor, 5-7
- finding the monitor type, 5-18
- finish, 19-3
- flicker, cause of in animation, 6-2
- floating point calculations, 7-5
- floating point precision, 2-16
- fog, 13-10 through 13-14
 - density, 13-12
 - equation, 13-13
 - modes, 13-14
 - per-pixel, 13-12
- fog characteristics, 13-12
- fogvertex, 13-10, 13-14
- font
 - creating, 3-7 through 3-10
 - selecting, 3-12
- Font Manager Library, 1-4
- fonts, 3-7 through 3-14
- frame buffer, 4-3, 4-17, 6-1
 - standard, 10-2
- frame buffers, 10-1 through 10-7
 - RealityEngine, 10-2
- frame rate, 6-3
- front-facing polygons, 2-24
- front buffer, 6-1
- frontbuffer, 6-2
 - zdraw, 8-10
- frontface, 8-22
- frustum, 7-5, 7-9, 7-10

G

- gamma correction, 4-23
- gamma ramp, 4-24
- gammaramp, 4-23, 4-24
- Gaussian filter for antialiasing, 15-35

- gconfig
 - doublebuffer, 6-2
 - multimap, 4-22
 - onemap, 4-22
 - RGBmode, 4-5
 - singlebuffer, 6-2
- generating a numeric identifier
 - for an object, 16-4
- genobj, 16-4
- gentag, 16-10
- geometric surface, 14-16
 - NURBS, 14-13
- geometry
 - bgn/end structure of, 2-2
 - definition, 2-1
- Geometry Engine, 17-2
- Geometry Pipeline, 1-1
 - feedback, 17-1
 - remote operation considerations, 19-3
- getbackface, 8-22
- getbuffer, 6-7
- getbutton, 5-8
- getcmmode, 4-22
- getcolor, 10-5
- getcpos, 3-4
- getcursors, 5-7, 10-21
- getdcm, 13-4
- getdev, 5-8
- getdisplaymode, 6-7
- getdrawmode, 10-7
- getfont, 3-14
- getgdesc, 1-7
 - GD_BITS, 4-3, 10-2
 - GD_BITS_NORM_SING_ALPHA, 15-7
 - GD_CIFRACT, 4-4
 - GD_DITHER, 4-4
 - GD_FOGVERTEX, 13-11
 - GD_LIGHTING_TWOSIDE, 9-17
 - GD_PIXPERSPECT, 18-33

- GD_POLYMODE, 2-30
- GD_ZMAX, 8-7
- GD_ZMIN, 8-7
- getgpos, 2-37, 7-3
- getlstyle, 2-10
- getlwidth, 2-11
- getmap, 4-22
- getmatrix, 7-29
- getmcolor, 4-18, 10-5
- getmonitor, 5-18
- getnurbscopy, 14-21
- getopenobj, 16-8
- getothermonitor, 5-19
- getscrbox, 7-29
- getscrmask, 7-28
- getting color information, 4-18
- getting font information, 3-14
- getting the size of the viewport, 7-27
- getvaluator, 5-7
- getvideo, 5-20
- getviewport, 7-27
- getwritemask, 10-10
- getzbuffer, 8-3
- gflush, 2-2, 19-2
- ghost devices, 5-13
- GLC_OLDPOLYGON, 2-31
- GLC_ZRANGEMAP, 13-3
- glcompat, 13-3
- GL Demos*, 14-1
- global state attributes, 1-10
- glresources, 5-2
- GL timers, 5-12
- GLX group of commands, 5-2
- Gouraud shading, 4-8, 4-10, 4-12, 10-7
 - color map mode, 4-17
 - performance, 4-9

- graphical object
 - creating, 16-2
 - definition, 16-1
 - sample, 16-3
- graphical objects, 16-1
- graphics development environment, 1-1
- Graphics Library, xxi
 - network transparency, 1-2
- Graphics Library, query version, 1-8
- graphics primitives, 2-1
- graphics server, 19-12
- graphics server daemon, 19-12
- gRGBcolor, 4-8
- gRGBmask, 10-10
- gross clipping, 3-4
- gselect, 12-8
- gsync, 6-8

H

- hardware
 - cursor, 10-17
 - feedback, 17-1 through 17-10
 - query, 1-7
- haze, 13-10
- hidden-surface removal, 8-1 through 8-26
- hierarchical drawing, 7-20
- hierarchical object, 16-5
- hierarchies, 16-1
- hierarchy
 - diagram, 16-6
- highlights on surfaces, 9-3
- hint
 - noport, 4-24
 - scrsubdivide, 18-45
 - texbind, 18-45
 - texdef2d, 18-44
 - texture caching, 18-45

- texture performance, 18-43
- hits, 12-1
- hostname, 1-3
- how a writemask works, 10-8

I

- iconsize, 5-14
- immediate mode, 2-1
- implicit representations, 14-2
- improving lighting performance, 9-22
- incident light, 9-2
- include files, 1-2
- independent variable, 14-2
- indirect light, 9-3
- inetd* daemon, 19-13
- infinite light source, 9-9
- infinite viewpoint, 9-10
- initnames, 12-5
- INPUTCHANGE, 5-3, 5-14
- input devices, 5-10 through 5-17
 - classes, 5-10
 - cursor, 5-13
 - keyboard, 5-13
- input event, 5-1
- input focus, 5-2
 - testing for change, 5-14
- instructions
 - how to create a cursor, 10-19
 - how to draw a NURBS surface, 14-14
 - how to draw old-style surface patches, 14-33
 - how to set up depth-cueing, 13-2
 - how to set up fog, 13-11
 - how to set up lighting, 9-4
 - how to set up picking, 12-2
 - how to set up queueing, 5-3
 - how to set up texture mapping, 18-6

- how to use man pages, xxv
- how to use sample programs, xxii
- Internet, 19-12
- interpolation
 - texture, 18-38
- interrupts limited for remote operation, 19-5
- IRIS-4D/GT/GTX feedback, 17-4
- IRIS-4D/VGX
 - clearing of z-buffer, 8-9
 - double-buffered overlay/underlay, 10-7
 - feedback, 17-7
 - fog, 13-10
 - mesh handling, 2-28
 - stenciling, 8-16
 - subpixel, 15-4
 - swapping multiple buffers, 6-3
- IRIS Font Manager, 3-1
- IRIS Indigo
 - allows local lights in color map mode, 9-25
 - backface removal, 8-21
 - dithering, 4-4
 - feedback, 17-6
 - fog, 13-10
 - no overlay/underlay on starter system, 10-1
 - pixel formats, 11-3
 - querying for perspective correction of texture, 18-33
 - texture perspective correction in SW, 18-32
 - z-buffer in software, 8-2
- IRIX, 1-1
- isobj, 16-4
- isqueued, 5-4
- istag, 16-9
- izoom, 18-29

J

- jumps limited for remote operation, 19-5

K

keepaspect, 7-6

kernel

filter, 18-20

keyboard

ringing the bell, 5-17

setting duration of bell, 5-17

turning on/off key click, 5-16

turning on/off lights, 5-16

keyboard device, 5-13

knot multiplicity, 14-8

knots, 14-5, 14-8

knot sequence, 14-8

L

-lc_s, 1-4

-lfm_s, 1-4

-lgl_s, 1-4

-lm_s, 1-4

-lsun, 1-4

labeling dial and button box indicators, 5-17

lampoff, 5-16

lampon, 5-16

LCOLOR, 9-9

Level-of-Detail, 18-24, 18-29

library

shared C, 1-4

shared Graphics Library, 1-4

light

ambient, 9-4, 9-9

attenuation, 9-14

emitted, 9-4

incident, 9-2

reflected, 9-2

wavelength, 9-2

lighting, 9-1 through 9-27

binding, 9-11

changing currently bound conditions, 9-13

defaults, 9-13

enabling, 9-11

how calculated, 9-6

in color map mode, 9-24

moving a light from frame to frame, 9-13

performance, 9-22

performance of updates, 9-19

two-sided, 9-18

lighting model, 9-10

light source

targets, 9-11

light sources, 9-9

limitations of lighting in color map mode, 9-24

linear interpolation of texture, 18-38

line of sight, 7-13, 7-14

lines

antialias, 15-15

old-style, 2-39

style, 2-10

width, 2-11

linestyle

definition, 2-10

specifying, 2-10

linewidth, 2-11

linewidthf, 2-11

linking, 1-4

Live Video Digitizer, 5-21

lmbind, 9-12, 9-21

LMC_AD, 9-20

LMC_AMBIENT, 9-20

LMC_COLOR, 9-20

LMC_DIFFUSE, 9-20

LMC_EMISSION, 9-20

LMC_NULL, 9-20

LMC_SPECULAR, 9-20

lmcolor, 9-19

performance, 9-19

- lmdef, 9-7, 9-8, 9-12, 9-14, 9-21
- LMNULL, 9-7
- loadmatrix, 7-29
- loadname, 12-4
- local host, 1-3
- LOCALVIEWER, 9-10
- LOCALVIEWER performance, 9-23
- local viewpoint, 9-10
- LOD, 18-24, 18-29
- logicop, 15-4
- lookat, 7-12, 7-14
- lrectread, 11-6, 11-16, 18-10
- lrectwrite, 11-7
- lRGBrange, 13-4
- lsetdepth, 8-7, 13-3, 13-5
- lshaderange, 13-4, 13-5, 13-10
- lsrepeat, 2-11

M

- makeobj, 16-2
- maketag, 16-9
- makewhatis*, xxvi
- making a light move from frame to frame, 9-13
- man*, xxv
- man pages, xxv
- mapcolor, 4-16, 10-5, 13-5
- mapw, 16-13
- mapw2, 16-13
- mask
 - linestyle, 2-10
 - pattern, 2-16
- material
 - defining, 9-8
 - different front and back, 9-18
 - fast updates, 9-18
 - transparent, 9-21

- matrix mode, 7-19
- matrix multiplication, 7-19
- maximum z value, querying for, 8-7
- MAXLIGHTS light sources limit, 9-11
- memory management
 - objects, 16-12
 - texture, 18-45
- meshes 2-21 through 2-28
 - changing vertex sequence, 2-23
 - drawing, 2-21
 - vertex sequence, 2-22
- minification filters, 18-17
- minimum z value, querying for, 8-7
- MIPmap
 - filter kernel, 18-20
 - quadlinear, 18-18
 - trilinear, 18-18
- mixed-model programming, 5-2
- mmode, 7-20
 - for fog, 13-11
- MTEXTURE, 18-33
- pushmatrix, 7-21
- mode
 - color map, 4-15 through 4-20
 - double buffer, 6-1, 6-2
 - fog, 13-14
 - for bitplanes, 10-5
 - for normal frame buffer, 10-6
 - multimap, 4-22
 - onemap, 4-22
 - querying color, 4-8
 - querying for display, 6-7
 - RGB, 4-5 through 4-15
 - setting up for animation, 6-2
 - single buffer, 6-1, 6-2
- modeling transformations, 7-16 through 7-19
- ModelView matrix, 7-3, 7-19, 7-29, 9-11, 9-13, 9-22

- monitor
 - color display, 4-2
 - other types, 5-19
 - querying for type, 5-18
 - setting type, 5-18
- Motif, 5-2
- move, 2-39
- MPROJECTION, 7-19
- msalpha, 15-47
- mspattern, 15-45
- mssize, 15-38
- mswapbuffers, 6-3
- MTEXTURE, 7-19
- multimap mode, 4-22
- multimatrix mode in lighting, 9-11
- multiple server I/O, 5-2
- multisampling, 15-37 through 15-47
- multmatrix, 7-29
- MVIEWING, 7-19

N

- name stack, 12-2, 12-4
- naming the output file, 1-4
- network-transparent feature of GL, 1-2
- network-transparent GL, 19-1 through 19-16
 - callback limit, 19-5
 - configuration, 19-12
 - connection, 19-4
 - DISPLAY, 1-2
 - error messages, 19-13
 - limitations, 19-5
 - linking, 19-2
 - linking for NIS, 1-4
 - non-IRIS hosts product, 19-2
 - sample application, 19-1
 - server, 1-3
- Network Information Service, 1-4, 19-12

- network transparency, 19-1
- newtag, 16-9
- NIS, 1-4, 19-12
- noise, 5-7, 5-12
- non-IRIS hosts, 19-2
- non-recommended subroutines, 2-37 through 2-42
- Non-uniform Rational B-splines, 14-1
- non-uniform scaling, 7-18
- noport, 4-24
- normal, current, 9-5
- NORMALDRAW, 10-6
 - swapping buffers in, 6-4
 - writemasks, 10-9
- normal frame buffer modes, 10-6
- normalized coordinate system, 7-3
- normals, 9-5
 - non-unit-length, 9-6
- NTSC, 5-21
- NURBS, 14-1 through 14-27
 - circle, 14-12
 - color surface, 14-17
 - conic sections, 14-12
 - cross-plot, 14-4
 - culling, 14-21
 - curve as a trimming curve, 14-20
 - curves, 14-11 through 14-13
 - definition, 14-11
 - enabling error messages, 14-21
 - formula for size of control point array, 14-14
 - further reading, 14-27
 - geometric surface, 14-16
 - offset in control point array, 14-15
 - piecewise linear trim curve, 14-20
 - properties, 14-21 through 14-22
 - surfaces, 14-13 through 14-18
 - tessellation, 14-21
 - texture surface, 14-17
 - trimming, 14-18 through 14-21
 - weight, 14-10

nurbscurve, 14-11
nurbssurface, 14-13

O

-o, 1-4
objdelete, 16-10
object
 closing a definition, 16-2
 creating, 16-2
 deleting, 16-4
 drawing, 16-4
 editing, 16-8
 hierarchy, 16-5
 identifying by number, 16-4
 memory management, 16-12
 tags, 16-9
 testing for existence, 16-4
object coordinate system, 7-2
objinsert, 16-10
objreplace, 16-11
offset, 14-15
old-style
 curves, 14-28, 14-28 through 14-33
 drawing, 2-30 through 2-42
 lines, 2-39
 pixels, 11-16
 points, 2-38
 polygons, 2-40
 polygon subroutines, 2-41
 surfaces, 14-28, 14-33 through 14-34
on-line man pages, xxv
onemap mode, 4-22
opening a window, 1-6
operating system, 1-1
order of pixel operations, 11-16
order of the polynomial, 14-5
order of transformations, 7-18, 7-19
order of vertices in lighting, 9-5

origin
 cursor, 10-20
ortho, 7-10, 7-11
ortho2, 2-4, 7-11, 12-3
orthographic projection, 7-4, 7-10
output file
 naming, 1-4
OVERDRAW, 10-6
 swapping buffers in, 6-4
 writemasks, 10-9
overlapping polygons, 8-2
overlay
 bitplanes, 10-3
 definition, 10-1
 non-recommended routines, 10-7
 user-defined, 10-15
overlay, 10-15

P

packing pixel data, 11-10, 11-14
PAL, 5-21
parameter, 14-2
parameterization, in textures, 18-33
parametric bicubic surface, 14-33
parametric representations, 14-2
parametric surface, 14-13
patterns, 2-16
pclos, 2-40
pclose warning, 2-40
per-pixel fog, 13-12
performance
 animation, 6-6
 font, 3-1
 Gouraud shading, 4-9
 improving lighting, 9-22
 lmcolor limitations, 9-19
 optimizing polygon, 2-12

- polygons, 18-43 through 18-46
 - texture alpha, 18-45
 - two-sided lighting, 9-23
- permission for connections, 19-4
- Personal IRIS
 - 8-bit pixel formats, 11-3
 - dithering, 4-4
 - feedback, 17-6
 - no overlay/underlay on B-bit models, 10-1
 - set Gouraud or depthcue for dithering, 4-4
 - speeding up `czclear`, 8-9
- perspective, 7-5
- perspective projection, 7-4
- phosphors, 4-2
- `pick`, 12-2
- picking, 12-1 through 12-8
 - size of region, 12-4
- `picksize`, 12-4
- piecewise linear trimming curve, 14-20
- piecewise polynomial, 14-5
- pixel, 4-2, 4-4, 8-23
 - centering, 15-4
- pixels
 - accessing, 11-2
 - centering, 11-4
 - centering on integers, 7-11
 - changing fill directions, 11-12
 - copying, 11-7
 - customizing operations, 11-10
 - formats, 11-2
 - formats of IRIS Indigo, 11-3
 - high-performance reading/writing, 11-3
 - old-style subroutines, 11-16
 - order of operations, 11-16
 - packing/unpacking, 11-14
 - setting read source, 11-4
 - writing, 11-7
- `pixmode`, 11-10
- `PM_EXPAND`, 11-11
- `PM_OFFSET`, 11-16
- `PM_SHIFT`, 11-10
- `PM_SIZE`, 11-14
- `PM_STRIDE`, 11-13
- `pmv`, 2-40
- `pntsize`, 2-7
- `pntsizef`, 2-7
- `pntsmooth`, 15-15
 - color map mode, 15-11
- point-sampled polygons, 2-17 through 2-20
- point and click interface, 12-1
- point light source, 9-9
- points
 - antialiased color map, 15-11
 - drawing, 2-7
 - old-style, 2-38
 - size, 2-7
- `polarview`, 7-12, 7-13
- `polf`, 2-41
- polling, 5-2, 5-7 through 5-10
 - button, 5-8
 - multiple valuator, 5-8
 - valuator, 5-7
- `poly`, 2-41
- polygon
 - antialiased, 15-22
 - bowtie, 2-15
 - concave, 2-13
 - convex, 2-12
 - definition, 2-12
 - display anomalies, 2-20
 - distortion, 2-16
 - drawing, 2-15
 - fat, 2-19
 - fill patterns, 2-16
 - front-facing, 2-24
 - Gouraud shaded, 4-8
 - non-planar, 2-16
 - old-style, 2-40
 - optimizing performance, 2-12

- outlined in old-style drawing, 2-31
- overlapping, 8-2
- point-sampled, 2-17 through 2-20
- rendering, 2-29
- simple, 2-12
- true area of, 2-19
- polyline
 - definition, 2-8
 - drawing, 2-8
- polymode, 2-29
- polynomials, 14-5
- pop-up menu callbacks
 - limited for remote operation, 19-5
- pop-up menus, 10-3
- popmatrix, 7-21
- popname, 12-5
- popviewport, 7-28
- POSITION, 9-9, 9-17
- position of a light source, 9-10
- precision in hardware calculations, 2-16
- primitive
 - character, 3-2
 - lighted, 9-4
 - line, 2-8
 - NURBS, 14-11
 - overlapping, 15-13
 - point, 2-7
 - polygon, 2-12
 - q-strip, 2-21, 2-27 through 2-28
 - smooth, 15-10
 - t-mesh, 2-21 through 2-27
- primitives, 2-1, 2-6
- program relinking to run remotely, 19-2
- projection
 - orthographic, 7-4, 7-10
 - perspective, 7-4
- Projection matrix, 7-5, 7-19, 7-30
- projection transformations, 7-4 through 7-12
 - for picking, 12-3
 - window, 7-9

- properties of NURBS, 14-21
- pruning, 16-5
- PUPDRAW, 10-6
- pushattributes/popattributes
 - when calling objects, 16-5
- pushmatrix, 7-21
- pushname, 12-4
- pushviewport, 7-28
- pwlcure, 14-20
- PYM_FILL, 2-29
- PYM_HOLLOW, 2-30
- PYM_LINE, 2-29
- PYM_POINT, 2-29

Q

- q-strips, 2-27 through 2-28
 - definition, 2-21
 - reducing to triangles, 2-28
- qdevice, 5-4, 5-13
- qenter, 5-4
- QFULL, 5-3
- qgetfd, 5-5
- qread
 - reading the queue, 5-5
 - remote, 19-5
- qreset, 5-3, 5-5
- qtest, 5-5
- quadlinear MIPmap, 18-18
- queuing, finding out if a device is queued, 5-4
- query
 - alpha bitplanes, 15-7
 - current linestyle, 2-10
 - depth-cueing, 13-4
 - font information, 3-14
 - system version, 1-7

- queue, 5-2
 - creating entries, 5-4
 - emptying, 5-3
 - limit, 5-3
 - reading, 5-5
 - reading multiple entries, 5-5
 - resetting, 5-5
 - testing for event, 5-5
- queueing, 5-2, 5-3 through 5-7
 - disabling, 5-4
 - enabling, 5-4
 - how to set up, 5-3
 - keyboard, 5-13
 - maximum efficiency, 5-3
 - window manager events, 5-14
- quitting a window, 5-14

R

- Raster Manager (RM) boards, 15-37
- rational, 14-11
- readdisplay, 11-5
- readfds*, 5-6
- reading pixels, 11-4
- reading location of, 5-6
- reading man pages, xxv
- reading multiple queue entries, 5-5
- reading video registers, 5-20
- README for sample programs, xxii
- readsource, 11-4
- RealityEngine
 - antialiasing, 15-36 through 15-47
 - bitplanes, 10-16
 - color, 4-5
 - color map size, 4-7
 - feedback, 17-8
 - fog, 13-10
 - framebuffers, 10-2
 - multisample buffer, 10-2

- stenciling, 8-16
- stereo buffering, 10-4
- swapbuffers, 6-3
- z-buffer size, 8-2
- recording events, 5-12
- rectangle subroutines, 2-32
- rectangles, drawing, 2-32
- rectcopy, 11-7
- rectread, 11-5
- rect/rectf, 2-32
- rectwrite, 11-7
- rectzoom, 11-7
- REDRAW, 5-3, 5-14
- REDRAWICONIC, 5-14
- reducing graphics jerkiness
 - in remote applications, 19-3
- reflectance, 9-3
 - diffuse, 9-3
 - specular, 9-3
- reflected light, 9-2
- reflection mapping, 18-34
- remote
 - configuration, 19-12
 - connection, 19-4
 - error messages, 19-13
 - interrupts, 19-5
 - jumps, 19-5
- remote display of graphics, 19-1
- REMOTEHOST, 19-4
- removing backfacing polygons, 8-22
- removing frontfacing polygons, 8-22
- rendering
 - averaging with accumulation, 15-31
 - bowtie polygons, 2-16
 - concave polygons, 2-13
 - improving polygon performance, 2-31
 - into 2 buffers, 6-3
 - NURBS, 14-21
 - polygons, 2-29

- resetting the queue, 5-5
- resolution of the z-buffer, 8-3
- RGB mode, 4-5 through 4-15
 - antialiasing, 15-13
 - depth-cueing, 13-6
 - double buffering in, 6-2
 - writemasks, 10-9
- RGBmode, 4-5
- RGBsize, 15-41
- RGB triple, 4-2, 4-5, 4-7
- RGBwritemask, 10-9
- right-hand rule, 2-24, 9-5
- ringbell, 5-17
- ringing the keyboard bell, 5-17
- rlogin*, 19-4
- rot, 7-17
- rotate, 7-17
- round-off errors, 11-4
- roundoff error, 2-4

S

- sample program
 - aliasing, 15-2
 - accumulation, 15-32
 - color map line, 15-17
 - points in color map mode, 15-11
 - RGB mode line, 15-19
 - RGB mode points, 15-13
 - RGB polygon, 15-22
 - RGB polygon corrected, 15-27
 - RGB polygon patch, 15-24
- blending, 15-9
- cursors, 10-21
- depth-cueing, 13-7
- drawing a hexagon, 2-15
- drawing a polygon, 2-9
- drawing lines, 2-5, 2-8
- drawing meshes, 2-25

- drawing old-style rectangles, 2-33
- drawing points, 2-7
- drawing with writemasks, 10-12
- feedback, 17-8
- NURBS, 14-22
- object editing, 16-11
- picking, 12-5
- selecting, 12-9
- vertex subroutines, 2-4
- writemasks, 10-10
- sample programs
 - where located, xxii
- scale, 7-18
- scaling of z coordinates, 8-7
- sclear, 8-19
- scrbox, 7-28
- screen
 - setting blanking time, 5-18
 - turning on/off, 5-18
- screen boxes, 2-33
- screenmask, 3-3, 7-27
- scrmask, 7-27, 11-7
- scrsubdivide, 18-33, 18-38 through 18-40
- searching man pages by key word, xxv
- select*, 5-5
- selecting, 12-8 through 12-10
- selecting a bitplane for drawing, 10-1
- selecting region, 12-8
- server, 1-3
- servers, 19-1
- setbell, 5-17
- setcursor, 10-21
- setdblights, 5-17
- setlinestyle, 2-10
- setmap, 4-22
- setmonitor, 5-18
- setnurbsproperty, 14-21
- setting screen blanking time, 5-18

- setting the duration of keyboard bell, 5-17
- setting the monitor type, 5-18
- setting up lighting, 9-4
- setvaluator, 5-16
- setvideo, 5-19
- shademodel, 4-9
- shademodel(FLAT), 4-9
- shademodel(GOURAUD), 4-9
- shared Graphics Library, 1-4
- shared library, 1-2
 - C, 1-4
 - for network-transparent GL, 1-2
- Sharpen, 18-23 through 18-27
- shifting pixel data, 11-10
- SHININESS, 9-8
- simple polygon, 2-12
- simultaneous clearing
 - of color and z-buffer, 8-8
- singlebuffer, 6-2
- single buffer mode, 6-1, 6-2
- sizing the viewport, 7-26
- SkyWriter
 - clearing of z-buffer, 8-9
 - double-buffered
 - overlay/underlay, 10-7
 - fog, 13-10
 - mesh handling, 2-28
 - per-pixel fog, 13-12
 - perspective correction
 - of texture in hardware, 18-33
 - stenciling, 8-16
 - subpixel, 15-4
 - swapping multiple buffers, 6-3
 - texture perspective correction, 18-32
 - TX_MIPMAP_TRILINEAR filter, 18-19
- sleep*, 2-6
- smoke, 13-10
- Spaceball device, 5-15
- SPECULAR, 9-8

- specular reflectance, 9-3
 - defining for material, 9-8
 - depends on viewpoint, 9-8
- spline, 14-5
- SPOTDIRECTION, 9-16
- SPOTLIGHT, 9-16
- spotlight, 9-16
 - attenuation, 9-17
 - direction, 9-16
- sprintf*, 4-7
- SRC_AUTO, 11-4
- SRC_BACK, 11-4
- SRC_FRAMEGRABBER, 11-4
- SRC_ZBUFFER, 11-4
- SS_DEPTH, 18-39
- stack matrix, 7-20
- STARTTAG, 16-9
- stencil, 8-16
- stenciling, 8-16 through 8-21
- stencil planes, 8-18
 - clearing, 8-19
 - enabling, 8-19
- stensize, 15-41
- stensize, 8-18
- stereo buffering, 10-4
- stowed windows, 5-14
- structure, using offsets to specify data in, 14-15
- strwidth, 3-5
- subimage, 11-13, 18-29
- subpixel, 15-4, 15-10
- subpixel accuracy, 15-4 through 15-5
- surface, transparent, 9-21
- surface normals, 9-5
- surface patch, 14-33
- surfaces, old-style, 14-28, 14-33 through 14-34
- swapbuffers, 6-3
- swapinterval, 6-7

- swapping buffers, defining interval for, 6-7
- swapping multiple buffers, 6-3
- swaptmesh, 2-23, 2-24
- swimming effect of texture, 18-37
- swritemask, 8-19

T

- 3-D textures, 18-4
- t-mesh, 2-21 through 2-27
 - definition, 2-21
- t2d, 18-33
- t2f, 18-33
- t2i, 18-33
- t2s, 18-33
- tags, 16-9
- TCP socket connections, 19-12
- tessellation
 - controlling the fineness of for NURBS, 14-21
 - definition, 14-21
- testing a window
 - for closure, 5-14
 - for quitting, 5-14
 - for stowing, 5-14
 - icon needed, 5-14
 - redraw needed, 5-14
- testing for an existing object, 16-4
- testing for button input, 5-6
- testing for change of input focus, 5-14
- testing the queue for events, 5-5
- tevdef, 18-40
- texbind, 18-11
- texdef2d, 18-11
- texdef3d, 18-11
- texels, 18-3
- texel size, 18-13
- texgen, 18-33

- text, drawing, 3-2
- texture, 18-1 through 18-50
 - alpha hints, 18-45
 - automatic generation, 18-33 through 18-34
 - blending, 18-41
 - blurring, 18-21
 - components, 18-7
 - contour, 18-35
 - coordinates, 18-33 through 18-35
 - decals, 18-42
 - environment, 18-40 through 18-42
 - filters, 18-16 through 18-21
 - format of image array, 18-9
 - image, 18-6
 - interpolation, 18-38
 - look-up tables, 18-36
 - magnification, 18-16
 - memory management, 18-45
 - minification, 18-16, 18-17
 - MipMap filter, 18-17 through 18-21
 - MipMap performance, 18-44
 - NURBS surface, 14-13, 14-17
 - performance, 18-43 through 18-46
 - perspective correction, 18-32
 - reflection mapping, 18-34
 - repeating, 18-12
 - scrsubdivide hints, 18-45
 - setting up, 18-6
 - swimming, 18-37 through 18-39
- texture mapping
 - definition, 18-3
- TG_CONTOUR, 18-34
- TG_LINEAR, 18-34
- TG_SPHEREMAP, 18-34
- tie, 5-6
- timer devices, 5-12
- tokens, 19-2
 - window manager, 5-14
- transformation, user-defined, 7-29
- transformation matrices, 7-19
- transformation matrix, 7-16, 7-19

- transformations, 7-2
 - order of, 7-18, 7-19
- translate, 7-17
- transparency, 8-23, 9-21
 - blending, 15-5
- transparent surfaces, 9-21
- tree, 16-6
- trilinear MIPmap, 18-18
- trimming a NURBS surface,
 - 14-18 through 14-21
- trimming curves, 14-18
 - orientation, 14-18
 - piecewise linear, 14-20
- trimming loop, 14-18
- turning on/off
 - cursor, 5-6
 - depth-cueing, 13-4
 - dial and button box lights, 5-17
 - keyboard click, 5-16
 - keyboard lights, 5-16
 - screen, 5-18
- TV_BLEND, 18-40, 18-41
- TV_DECAL, 18-41, 18-42
- TV_MODULATE, 18-40, 18-41
- twist, 7-13, 7-14
- two-sided lighting, 9-17
 - performance, 9-23
- TWOSIDE, 9-17
- TX_MAGFILTER, 18-12
- TX_MINFILTER, 18-12
- TX_REPEAT, 18-12
- TX_TILE, 18-13
- TX_WRAP, 18-12

U

- UNDERDRAW, 10-6
 - swapping buffers in, 6-4
 - writemasks, 10-9
- underlay
 - bitplanes, 10-3
 - definition, 10-1
 - non-recommended routines, 10-7
 - user-defined, 10-15
- underlay, 10-15
- unpacking pixel data, 11-10, 11-14
- unqdevice, 5-4
- updating active materials, 9-18
- user-defined transformation, 7-29
- user input in a GL program, 5-1
- user interface, 5-1

V

- valuator
 - names of, 5-12
 - noisy, 5-7
 - polling, 5-7
 - polling multiples, 5-8
- version, querying, 1-7
- vertex, 2-1
 - normals, 2-24
 - order for front-facing polygons, 2-24
 - subroutines, 2-2, 2-3
- vertex ordering, importance of in lighting, 9-5
- video, 5-17 through 5-21
 - enabling the LVD option, 5-21
 - formats, 5-21
 - reading registers, 5-20
 - setting hardware registers, 5-19
- videocmd, 5-21
- viewing transformation, 7-3
- viewing transformations, 7-12 through 7-16

- viewpoint
 - defining, 7-13
 - for lighting, 9-10
- viewport, 3-3, 7-26 through 7-29
- viewport, 7-26
- volume rendering, 18-5

W

- wavelength of light, 9-2
- weight of control points, 14-10
- window
 - opening, 1-6
 - quitting, 5-14
 - testing for closure, 5-14
 - testing for iconification, 5-14
 - testing if redraw needed, 5-14
- window, 7-9
- window coordinate system, 7-3
- window manager
 - 4Dwm*, 1-2, 1-3
 - queueing events from, 5-14
- window manager tokens, 5-14
- WINFREEZE, 5-14
- WINQUIT, 5-14
- WINSHUT, 5-14
- WINTHAW, 5-14
- wireframe, definition, 2-1
- wmpack, 10-10
- world coordinate system, 7-3
- writemask, 10-7
 - definition, 10-7
 - how it works, 10-8
- writemask, 10-9, 11-7
- writemasks, 10-7 through 10-15
- writing pixels, 11-7
- writing to the z-buffer, 8-10

X

- X client, 1-2
- X input model, 5-2
- xman*, 1-2
- X server, 1-2, 1-3, 5-2
- xterm*, 1-2
- Xt routines, 5-2
- X Window System, 1-2, 5-2

Z

- z-buffer, 8-2 through 8-15
 - changing comparison test, 8-14
 - clearing, 8-8
 - enhancing resolution of, 8-3
 - writing directly to, 8-10
- zbsize, 15-41
- zbuffer, 8-3
- z coordinates, scaling, 8-7
- zdraw, 8-10
- zfar, 8-3
- zfar*, 13-5
- znear, 8-3
- znear*, 13-5
- z values for depth-cueing, 13-3
- zwritemask, 8-15
- z-buffer
 - zwritemask, 8-15